


## Panel mounted receptacle with TwinCONTACT - Part no. 1740



- screwless spring terminals
- suitable for through wiring
- 20° inclination
- 32 A receptacles are designed for adding an auxiliary contact switch

### Technical information

|                       |                         |
|-----------------------|-------------------------|
| Ampere                | 32 A                    |
| Poles                 | 4 p                     |
| Voltage               | 400 V                   |
| Earth position        | 6 h                     |
| Hertz                 | 50-60 Hz                |
| Connection technology | Screwless - TwinCONTACT |
| Contact               | standard                |
| Protection type       | IP 44                   |



| Drawing<br>1 MB 465 | Amp.<br>Poles   | 16   |     |     | 32  |     |     |
|---------------------|---|------|-----|-----|-----|-----|-----|
|                     |   | 3    | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm          | a   | 73,5 | 100 | 100 | 100 | 100 | 100 |
|                     | b   | 64   | 92  | 92  | 92  | 92  | 92  |
|                     | c   | 52   | 58  | 58  | 61  | 61  | 60  |
|                     | d   | 60   | 85  | 85  | 85  | 85  | 85  |
|                     | e   | 52   | 77  | 77  | 77  | 77  | 77  |
|                     | f   | 5,5  | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
|                     | g.  | 7    | 8   | 8   | 8   | 8   | 8   |
|                     | g.1   | 2    | 2   | 2   | 2   | 2   | 2   |
|                     | h   | 79   | 100 | 100 | 103 | 103 | 105 |
|                     | k   | 31   | 31  | 31  | 44  | 44  | 54  |
|                     | l   | 52   | 55  | 65  | 70  | 70  | 73  |
|                     | l1  | 60   | 63  | 72  | 82  | 82  | 85  |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1,5  | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
|                     |   | -4   | -4  | -4  | -6  | -6  | -6  |